


PN 10/16 - DN 50...300

KAT-A 1332-G-Lug

Product characteristics and benefits

- Resilient seated in accordance with EN 13774 (DIN 3352 - 4A)
- Face-to-face length acc. to EN 558-1, basic series 20 (DIN 3202 / K1)
- Lug-type for flanges acc. to EN 1092-2
- Centric disk, mounted in three maintenance-free bearing bushes
- For bolting between pipe flanges
- Replaceable rubber sleeve with integrated seal for functionally reliable use for flared flanges, welding flanges, PE flanges as well as loose flanges with V-collar
- Stable sealing seat due to collar with vulcanized support ring
- Vacuum tight up to 1 Torr
- Tight in both flow directions
- For gases according to DVGW Guideline G 260

Materials

- Body: Ductile iron EN-GJS-400-15 (GGG-40)
- Disk: Stainless steel 1.4408
- Shaft end: Stainless steel 1.4021
- Collar: NBR

Corrosion protection


- Body: Internally and externally epoxy coated

Versions

- Standard version as described
- With electric actuator
- With notched hand lever
- With pneumatic actuator
- With worm gear unit and handwheel
- Bigger sizes available on request
- Optimised version for low working pressure 5 bar available

Field of application

- Installation in plants


Tests and approvals

- Final inspection test acc. to DIN 3230-5 PG3
- DVGW tested and registered

Note

For proper installation and safe operation please follow the installation and operation instructions:
KAT-B 1331

Gas pipeline applications

DN	PN	Maximum operating pressure [bar]	Maximum operating temperature for gasses to DVGW G 260 [°C]
50...300	16	16	50
200...300	10	10	50

Pressure test acc. to EN 12266

Test pressure body with water [bar]	Test pressure body with air [bar]	Test pressure seat with air [bar]
24	0.5	0.5
15	0.5	0.5

Gas system applications

DN	PN	Maximum operating pressure [bar]	Maximum operating temperature for gasses to DVGW G 260 [°C]
50...300	16	16	50
200...300	10	10	50

Pressure test acc. to EN 12266


Test pressure body with water [bar]	Test pressure body with air [bar]	Test pressure seat with air [bar]
24	0.5/17.6	0.5/17.6
15	0.5/17.6	0.5/17.6

VAG CEREX® 300-L Butterfly Valve

disk made of stainless steel - lug-type

Gas

Drawing



Technical data

PN 10

DN		200	250	300
A	[mm]	240	275	300
D	[mm]	252	301	356
E	[mm]	10	12	12
G	[mm]	188	239	288
L	[mm]	12	14	14
B	[mm]	175	205	230
D1	[mm]	268	323	377
E1	[mm]	56	56	79
E2	[mm]	75	75	95
F	[mm]	70	102	102
H	[mm]	70	91	111
H2	[mm]	270	305	340
H3	[mm]	195	195	295
H4	[mm]	262	-	-
H5	[mm]	300	-	-
ISO		F07	F10	F10
J	[mm]	19	24	24
K	[mm]	295	350	400
L1	[mm]	60	68	78
R	[mm]	200	200	300
SQ	[mm]	17	22	22
Number of blind thread holes		8	12	12
Thread M		M20	M20	M20
Weight of valve approx.	[kg]	22.5	26.8	37.4
Weight with notched hand lever	[kg]	23.5	-	-
Weight with gearbox approx.	[kg]	24.4	28.7	40.6



Technical data

PN 16

DN		50	65	80	100	125	150	200	250	300
A	[mm]	125	132	140	180	190	220	240	275	300
D	[mm]	87	102	112	142	161	201	252	301	356
E	[mm]	7	7	7	7	7	10	10	12	12
G	[mm]	31	51	69	91	115	149	188	239	288
L	[mm]	10	10	10	10	10	12	12	14	14
B	[mm]	72	80	87	113	123	155	175	205	230
D1	[mm]	98	114	132	156	185	216	268	323	377
E1	[mm]	48	48	48	48	48	48	56	56	79
E2	[mm]	66	66	66	66	66	66	75	75	95
F	[mm]	50	50	50	50	50	70	70	102	102
H	[mm]	5	12	19	27	37	52	70	91	111
H2	[mm]	155	160	170	210	220	250	270	305	340
H3	[mm]	120	120	120	120	120	180	195	195	295
H4	[mm]	140	146	155	195	205	238	258	-	-
H5	[mm]	225	225	225	225	225	305	305	-	-
ISO		F05	F05	F05	F05	F05	F07	F07	F10	F10
J	[mm]	12	12	12	16	16	19	19	24	24
K	[mm]	125	145	160	180	210	240	295	355	410
L1	[mm]	43	46	46	52	56	56	60	68	78
R	[mm]	125	125	125	125	125	200	200	200	300
SQ	[mm]	11	11	11	14	14	17	17	22	22
Number of blind thread holes		4	4	8	8	8	8	12	12	12
Thread M		M16	M16	M16	M16	M16	M20	M20	M24	M24
Weight of valve approx.	[kg]	2.7	3.2	4.3	6	7.3	9.5	22.5	26.8	37.4
Weight with notched hand lever	[kg]	3.4	3.8	5.0	7.1	8.0	10.5	23.5	-	-
Weight with gearbox approx.	[kg]	4.0	4.5	5.6	7.3	8.6	10.9	24.4	28.7	40.6